

MATERIAL SAFETY DATA SHEET SIMILAR TO OSHA FORM 20

SECTION 1.



**RUST AND SCALE REMOVER**

MANUFACTUER / DISTRIBUTOR:

GREEN POWER CHEMICAL

P.O. BOX 507 STANHOPE , NJ 07874

EMERGENCY TELEPHONE NUMBER – 1-800-932-9371

CHEMICAL NAME : RUST AND SCALE REMOVER

UPDATED : 01/18/2013

**SECTION II. HAZARDOUS INGREDIENTS/IDENTITY INFORMATION**

Hazardous Components	OSHA PEL	OTHER ACGIH TLV	PERCENT OPTIONAL
*Phosphoric Acid CAS# 7664-38-2	1 mg/m <sup>3</sup>	1 mg/m <sup>3</sup> 3 mg/m <sup>3</sup> (STEL)	25-50
**Nonylphenol Ethoxylate CAS#9016-45-9	NA	NA	<5
***Dipropylene Glycol Monomethyl Ether	100ppm	100ppm CAS#34590-94-8	

\*Phosphoric acid is subject to SARA section 311, 312, and 313. It is classified as an Immediate Health hazard. It may contain traces of listed chemicals from California Proposition 65: arsenic, cadmium, lead.

\*\*Nonylphenol Ethoxylate is listed with SARA Section 311 as Glycol Ethers. It is also subject to state Right To Know Regulations in Pennsylvania.

\*\*\*Dipropylene Glycol Monomethyl ether is subject to SARA Section 311/312 as an Immediate Health hazard and a Fir Hazard.

DOT Shipping Classification – Corrosive

Health Rating....3 Flammability....0 Reactivity....0

**SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS**

Boiling Point.....212 deg. F  
Vapor Pressure (mm Hg).....NA  
Vapor Density (air=1).....>1  
Solubility in water .....Complete  
Appearance and Odor: Clear liquid, fruity odor

Specific Gravity.....(H2O=1)>1  
Melting Point.....NA  
Evaporation Rate.....NA  
(Butyl Acetate = 1)

