#### Page: 1

# SAFETY DATA SHEET

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

## **TASC Powder M-8580**

	1. Identi	fication
Product Code: Product	T08	
Name:	TASC Powder	
Manufacturer Information	M-8580	
Company Name:	Green Power Chem	nical
	P.O. Box 507	
	Stanhope, NJ 0787	74
Emergency Contact:	Chemtel	(800)255-3924
Information: Intended Use:	Concentrated Alkali	ne Detergent
	For cleaning various	s metals in parts washers.

## 2. Hazards Identification

#### **GHS** Classification





Causes serious eye damage

Causes severe skin burns and eye damage

Skin Corrosion 1C H314 Eye Dam. 1 H318

#### **GHS Label Elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

## **GHS Precaution Phrases**

Danger. Causes serious eye damage. Causes severe skin burns.

## GHS Response Phrases

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

## Hazard-Determining Components:

Sodium Metasilicate Pentahydrate

Tetrasodium EDTA

## **Emergency Overview/Precautionary**

#### **Statements**

Do not breath dusts or mists.

Wear eye protection/face protection.

Wash thoroughly after handling.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

## OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

## **TASC Powder M-8580**

If in eyes:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/Doctor.

Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Wash contaminated clothing before reuse.

If swallowed: Rinse mouth. Do NOT induce vomiting.

## **OSHA Regulatory Status:**

This material is not classified as hazardous under OSHA regulations.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations

Unknown acute toxicity: 3% of the mixture consist of components of unknown toxicity.

## Classification System:

**NFPA Ratings:** 

# 300

HMIS Ratings: Planisol-M/TASC Powder M-8580 HEALTH 3 FLAMMABILITY 0 REACTIVITY 0 PERSONAL PROTECTION

Hazard(s) not otherwise classified (HNOC): None Known.

3. Composition/Information on Ingredients					
Hazardous Components (Chemical Name)		CAS# Concentration		RTECS (if applicable)	
1	Sodium carbonate	497-19-8	Prop %		
2.	Sodium meta silicate Pentahydrate	10213-79-3	•		
3.	Sodium Chloride	7647-14-5	Prop %	VZ4725000	
4.	Alcohol C9-11	68439-46-3	Prop %		
5.	Tetrasodium EDTA	64-02-8	Prop %	AH5075000	

## **Chemical Characterization:** Mixtures

Description: Mixture of substances listed below with non-hazardous additions.

# 4. First Aid Measures

## **Emergency and First Aid Procedures**

General Information: Immediately remove any clothing soiled by the product.

Eyes: Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Skin: Immediately wash with water and soap and rinse thoroughly. If skin irritation occurs, consult a doctor.

**Ingestion:** Rinse out mouth and then drink plenty of water. Do not induce vomiting. Drink copious amounts of water and provide fresh air. Immediately call a doctor.

**Inhalation:** Remove to fresh air. Dust in throat and nasal passages should clear spontaneously. Seek medical attention for discomfort or if coughing or other symptoms do not subside.

## Note to Physician

Treat symptomatically and supportively.

## Signs and Symptoms of Exposure

No further relevant information available.

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

**TASC Powder M-8580** 

	5. Fire Fighting	Measures
Flash Pt:	NP Method Used: Est	timate
Explosive Limits:	LEL:	UEL:
Autoignition Pt:	NP	
Fire FightingInstructions		

As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear to prevent contact with skin and eyes.

## Special hazards arising from the substance or mixture:

If incinerated, product will release the following toxic fumes: Oxides of Carbon, Nitrogen (NO<sub>x</sub>), Phosphorous, Silicon, Sodium and Hydrochloric acid gas.

## **Suitable Extinguishing Media**

CO<sub>2</sub> extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

## 6. Accidental Release Measures

## Steps To Be Taken In Case Material Is Released or Spilled

Use respiratory protective device against the effects of fumes/dust/aerosol. Avoid formation of dust. Avoid contact with skin, eyes, and clothing. Ensure adequate ventilation. Wear protective equipment. Keep unprotected persons away. **Environmental Protections:** Do not allow to enter sewers/surface or ground water.

## Methods and material for containment and cleaning up:

Powder and fragments should be cleaned up using a method that will avoid the generation of dust in the workplace atmosphere. The use of a vacuum cleaner fitted with an exhaust air filter fine enough to trap the dust is recommended. Dispose of the collected material according to regulations.

**Reference to other sections:** See Section 7 for safe handling. See Section 8 for personal protective equipment. See section 13 for disposal information.

## 7. Handling and Storage

## Precautions to Be Taken in Handling

Ensure good ventilation/exhaustion at the workplace.

## Precautions to Be Taken in

Store away from strong acids, strong bases, and strong oxidizing agents.

## Storing Requirements to be met by storerooms and receptacles:

Store in original container. No further relevant information about storing available.

## 8. Exposure Controls/Personal Protection

Additional information about design of technical systems: Control parameters: No further data; see section 7

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use local exhaust at filling zones and where leakage and dust formation is probable. Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep exposure limits in the air below TLV & PEL limits.

## Components with occupational exposure limits:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: The lists that were valid during the creation of this SDS were used as basis. Personal Protective Equipment and General Protective and Hygienic Measures:

The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages, and feed. Immediately remove all soiled and contaminated clothing and wash before reuse.

Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

TASC Powder M-8580

## **Breathing Protection**



Wear dust mask.

## **Eye Protection**



Wear tightly sealed goggles.

**Body Protection:** 



Wear protective work clothing.

## **Protection of Hands:**

#### Wear Protective Gloves



The glove material has to be impermeable and resistant to the product/substance/preparation. Due to missing tests no recommendation to the glove material can be given for the

product/preparation/chemical mixture. Select glove material based on penetration times, rates of diffusion, and degradation. The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer

**Penetration Time of Glove Material:** The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

# 9. Physical and Chemical Properties

Information on basic physical and chemical properties.				
Appearance:				
Form:	Powder			
Color:	White			
Odor:	Mild			
Odor threshold:	Not Determined.			
pH-Value:	>11.5			
Change in condition:				
Melting point/Melting range:	Not Determined			
Boiling point/Boiling range:	Not Determined			
Flash Point:	None			
Flammability (solid, gaseous):	Not Applicable			
Ignition Temperature:				
Decomposition temperature:	Not determined.			
Auto igniting:	Product is not self-igniting			
Danger of explosion:	Product does not present an explosion hazard.			
Explosion limits:	· ·			
Lower/Upper:	Not Determined.			
Vapor Pressure:	Not Determined			
Density:				
Relative Density:	Not Determined			
Vapor Density:	Not Determined			
Evaporation Rate:	Not Determined			
Solubility in / miscibility with:				
Water:	Soluble.			
Partition Coefficient (n-octanol/water):	Not Determined			
Viscosity:				
Dynamic:	Not Determined			
Kinematic:	Not Determined			
Solvent Content:				
Organic Solvents:	0.0%			
Solids Content:	95.4%			
Other Information:	No further relevant information available.			

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

TASC Powder M-8580

# **10. Stability and Reactivity**

Stable [X]

Reactivity:	
No information	available.

**Stability:** 

1

Thermal Decompostition /

**Conditions to Avoid:** 

No decomposition if used according to specifications.

Incompatible Materials:

Strong acids, strong bases, and strong oxidizing agents.
Possibility of Hazardous Reactions: Will occur [ ] Will not occur [X]

Unstable [

## Hazardous Decomposition Products:

Oxides of Carbon, Nitrogen (NOx), Phosphorous, Silicon, Sodium, and Hydrochloric acid gas.

**11. Toxicological Information** 

Information on Toxicological Effects:

#### Acute Toxicity:

LD/LC50 values that are relevant for classification: 497-19-8 Sodium Carbonate Oral LD50 4090 mg/kg (rat) LC50/96 hours 300 mg/l (Fathead Minnow) Inhalative 10213-79-3 Sodium Metasilicate Pentahydrate Oral LD50 845 mg/kg (rat) 7647-14-5 Sodium Chloride Oral LD50 3000 mg/kg (rat) LD50 >10000 mg/kg (rabbit) Dermal 64-02-8 Tetrasodium EDTA Oral LD50 630-1260 mg/kg (rat) **Primary Irritant Effect:** On the skin: Strong caustic effect on skin and mucous membranes. On the eye: Strong irritant with the danger of severe eye injury. Corrosive effect. Causes serious eye irritation. Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive Irritant Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach. **Carcinogenic Categories:** IARC (International Agency for Research on Cancer): Group 1 – Carcinogenic to humans Group 2A – Probably carcinogenic to humans Group 2B – Possibly carcinogenic to humans Group 3 – Not classifiable as to its carcinogenicity to humans Group 4 – Probably not carcinogenic to humans None of the ingredients are listed. NTP (National Toxicological Program): None of the ingredients are listed. **OSHA-CA** (Occupational Safety & Health Administration): None of the ingredients are listed.

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

**TASC Powder M-8580** 

# **12. Ecological Information**

Toxicity:

Aquatic Toxicity:

497-19-8 Sodium Carbonate

EC50 227 mg/l (daphnia)

7647-14-5 Sodium Chloride

EC50 1661 mg/l (Water Flea)

Persistence and Degradability: No further relevant information available.

Behavior in environmental systems:

Bioaccumulative Potential: No further relevant information available.

**Mobility in soil:** No further relevant information available.

Additional Ecological Information:

General Notes: Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Results of PBT and vPvB assessment:

**PBT:** Not applicable.

vPvB: Not applicable

Other adverse effects: No further relevant information available.

## **13. Disposal Considerations**

## Waste Treatment Methods and Recommendations:

Small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with Local Authority requirements.

**Uncleaned packaging recommendations:** Dispose of as unused product. Disposal must be made according to official regulations.

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

## **14. Transport Information**

## **Globally Harmonized System of Classification and Labelling**

Serious Eye Damage/Eye Irritation, Category 2B - Warning! Causes eye irritation. Causes Skin Irritation.

## LAND TRANSPORT (US DOT)

Not regulated as a hazardous material.

DOT Shipping Name	Not regulated as a hazardous material.	
DOT Hazard Class:	Not regulated as a hazardous material.	
UN/NA Number: Packing Group:	Not regulated as a hazardous material.	
LAND TRANSPORT	Not regulated as a hazardous material.	
(Canadian TDG) TDG Shipping	Not regulated as a hazardous material.	
Name	No information available.	

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

## **TASC Powder M-8580**

## **15. Regulatory Information**

#### SARA (Superfund Amendments and Reauthorization Act of 1986) Lists:

Sec.355:None of the ingredients are listed.Sec.313:None of the ingredients are listed.

#### TSCA (Toxic Substances Control Act) Lists:

•	· · · ·
497-19-8	Sodium Carbonate
7647-14-5	Sodium Chloride
68439-46-3	Alcohol C9-11
64-02-8	Tetrasodium EDTA

#### **California Proposition 65:**

Chemicals known to cause cancer: None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for females: None of the ingredients are listed.

Chemicals known to cause reproductive toxicity for males: None of the ingredients are listed.

Chemicals known to cause developmental toxicity: None of the ingredients are listed.

#### Carcinogenic Categories:

EPA (Environmental Protection Agency): None of the ingredients are listed.

TLV (Threshold Limit Value established by ACGIH): None of the ingredients are listed.

NIOSH-Ca (National Institute for Occupational Safety and Health): None of the ingredients are listed GHS Label Elements: The product is classified and labeled according to the Globally Harmonized System (GHS).

#### Hazard Pictograms:



Signal Word: Danger.

Hazard-determining components of labeling: Sodium Metasilicate Pentahydrate and Tetrasodium EDTA Hazard Statements: Causes severe skin burns and eye damage.

Precautionary Statements: Do not breath dusts or mists. Wear eye protection/face protection. Wash thoroughly after handling. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CONTROL CENTER/doctor. Specific treatment (see supplementary first aid instructions on this Safety Data Sheet). IF INHALED: Remove person to fresh air and keep comfortable for breathing. Wash contaminated clothing before reuse. If swallowed: Rinse moth. Do NOT induce vomiting. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

National Regulations: The product is subject to be classified according with the latest version of the regulations on hazardous substances.

State Right to Rhow.			
CAS#	<b>Chemical Name</b>	Concentration	<b>RTECS</b> (if applicable)
497-19-8	Sodium Carbonate	Prop%	
10213-79-3	Sodium Metasilicate Pentahydrate	Prop%	
7647-14-5	Sodium Chloride	Prop%	VZ4725000
68439-46-3	Alcohol C9-11	Prop%	
64-02-8	Tetrasodium EDTA	Prop%	AH5075000
All ingredients are l	isted		

All ingredients are listed.

Chemical Safety Assessment: A Chemical Safety Assessment has not been carried out.

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

TASC Powder M-8580

# **16. Other Information**

## **Company Policy or Disclaimer**

The information and recommendation in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

## Date of preparation / last revision: 01/01/19

#### Abbreviations and acronyms:

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road ADN: The European Agreement concerning the International Carriage of Dangerous Good by Inland Waterways. IMDG: International Maritime Code for Dangerous Goods. DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Cancer Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50% LD50: Lethal dose, 50% PBT: Persistent, Bioaccumulative, and Toxic VPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety **OSHA: Occupational Safety & Health** TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit

Acute Tox. 4: Acute toxicity, Hazard Category 4 Skin Corr. 1C: Skin corrosion/irritation, Hazard Category 1C Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2 STOT SE 3: Specific target organ toxicity – Single exposure, Hazard Category 3

\*NOTE: Hazard Determination System (HDS) rating are based on a 0-4 scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.

## \*Data compared to the previous version altered.