


SECTION I.



"CONCRETE GLEEM" POWDERED CLEANER DEGREASER

MANUFACTURER/DISTRIBUTOR: GREEN POWER, 800-932-9371 UPDATED: 2/21/13
 PO BOX: 507 Stanhope, NJ. 07874 151 SPARTA STANHOPE RD. HOPATCONG, NJ 07843
 EMERGENCY TELEPHONE NUMBER: (973)-770-5600 -1-800-932-9371
 CHEMICAL NAME AND SYNONYMS: N/A PROPRIETARY BLEND
 TRADE NAME AND SYNONYMS: "CONCRETE GLEEM" BIODEGRADABLE CLEANER/DEGREASER
 CHEMICAL FAMILY: BUILT FORMULA
 FORMULA: N/A BLENDED PRODUCT FRIENDLY TO THE ENVIRONMENT

SECTION II. HAZARDOUS INGREDIENTS THE LIST BELOW ARE IRRITANTS / NON TOXIC

	CAS#	%	TLV UNITS
BISODIUM Carbonate	479-19-8	Prop.	Not est.
Sodium Metasilicate Pentahydrate	6834-92-0	Prop	Not est.
Ethoxylated linier Alcohol	68439-46-3	Prop	Not est
LAS	25155-30-0	Prop	Not est

SECTION III. PHYSICAL DATA HMIS Ratings: Health 1 Flammability 0 Reactivity 0

BOILING POINT (F.): N/A° SPECIFIC GRAVITY: N/A
 VAPOR PRESSURE: N/A % VOLATILE BY WEIGHT: 10
 VAPOR DENSITY: N/A EVAPORATION RATE: = N/A
 SOLUBILITY IN WATER: Complete pH: 13.1
 APPEARANCE AND COLOR: WHITE POWDER

SECTION IV. FIRE AND EXPLOSION DATA

FLASH POINT: N/A
 EXTINGUISHING MEDIA: Noncombustible
 SPECIAL FIRE FIGHTING PROCEDURES: None
 UNUSUAL FIRE AND EXPLOSION HAZARDS: None
 FLAMMABLE LIMITS: Not established

SECTION V. HEALTH HAZARD DATA

Route(s) of entry INHALITON: YES SKIN: YES INGESTION: YES
 THRESHOLD LIMIT VALUE:
 EFFECTS OF OVER EXPOSURE: Causes skin and eye irritation. Harmful if swallowed, may cause severe mucousal damage and gastric distress. May cause systemic intoxication.
 EMERGENCY & FIRST AID PROCEDURES: FOR EYES: Flush with water for at least 15 minutes. Get medical aid.
 IF INGESTED: **Do not induce vomiting.** Give milk, egg white, gelatin or water. Get medical aid.
 CONDITIONS AGGRAVATED BY EXPOSURE: May aggravate existing dermatitis and irritate sensitive skin.

LISTED CARCINOGEN, MUTAGEN, TERATOGEN(INGREDIENT, SOURCE AMOUNT) :None

THERE ARE NO VOCs IN THIS FORMULA

SECTION VI. REACTIVITY DATA

STABILITY: Stable

CONDITIONS TO AVOID: None

INCOMPATIBILITY: Acids and oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon oxides and amines

HAZARDOUS POLYMERIZATION: Will not occur

SECTION VII. SPILL OR LEAK PROCEDURE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Vacuum, sweep or shovel into a suitable container for disposal.

WASTE DISPOSAL METHOD: Follow local, state, and federal regulations. **CONCRETE GLEEM** NOT CONSIDERED A HAZARDOUS WASTE under RCRA. RCRA HAZ. WASTE NOS. : N/A

SECTION VIII. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: Generally not required

VENTILATION (LOCAL/MECHANICAL/SPECIAL) : Local

PROTECTIVE GLOVES: Rubber or latex

EYE PROTECTION: Goggles of safety glasses with shields

OTHER PROTECTIVE EQUIPMENT: Rubber boots should be worn if standing in solution.

SECTION IX. SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE BETWEEN 40 AND 120 DEGREES F.

OTHER PRECAUTIONS: FOR SALE TO AND USE BY SERVICE PERSONNEL ONLY. KEEP OUT OF REACH OF CHILDREN. THOROUGHLY WASH ALL CONTAMINATED CLOTHING BEFORE REUSE.